



PO Box 1677
Vanderbijlpark
1900
South Africa
Tel/Fax: +27 16 987 1640

VAT No: 4190170243
Reg No: CK1997/57459/23

E-mail: boro@mweb.co.za
Website: www.metprotec.com

Product Bulletin **Corrogard® 45**

DESCRIPTION

Corrogard® 45 is different from normal rust prevention coatings in that it is water based or water dispersible and contains no oil, solvents or other harmful materials. They are non-hazardous and are outside the scope of the Volatile Organic Compounds (VOC) emission regulations of the Environment Protection Act. **Corrogard® 45** protects by direct contact with metal parts which have been coated by brush, dip, spray, etc. and allowed to dry. Designed for multi metallic protection of ferrous, copper, aluminium, galvanise and tinplate by means of contact, dip, spray etc.

PRODUCT BENEFITS

1. **Corrogard® 45** is used as a dilution in water ensuring a high coverage rate with consequent excellent cost effectiveness.
2. **Corrogard® 45** has been specifically designed to protect all commonly occurring metals including those with a cast iron content reduces inventory.
3. **Corrogard® 45** utilises only raw materials that are found in the FDA CFR21 list, hence it's safe and clean working nature.
4. **Corrogard® 45** can be applied by conventional spray equipment as a rapid application system or be implemented in the works process so as to be "in line," with the assembly.

APPLICATION

Corrogard® 45 is easily applied by brush, roller or conventional spray equipment. Parts may also be treated by immersion and allowed to drip dry. The product will find application wherever there is a need for corrosion protection of metal parts or equipment.

PACKING AND HANDLING

Corrogard® 45 is packed in 25 Kg drums. The product should be stored in a cool dry place out of direct sunlight. Minimise exposure by good industrial hygiene practices. Use the necessary personal protection equipment.